NESPRESSO.

PRODUCT DATA SHEET UMILK





	Model C	**Model D**
Colour:	Pure Cream	Pure Black
Nespresso Code:	U C55	U D55
RAL color reference:	RAL DESIGN 110 90 05	RAL DESIGN 15 00











U, the new automated machine from Nespresso: your coffee in one single gesture now available with an integrated milk solution

Key benefits:

- Automation
- Modular shape
- Milk recipes

Product features:

- **Innovative active slider**
- **Motorized Brewing Unit: automatic piercing, brewing and fully automatic ejection of used capsules**
- **3 pre-programmed cup sizes**
- **Drop stop system**
- **Automatic memorization of preferred cup size**
- **Integrated fresh milk frother for hot and cold recipes**
- Pure & Modular design: adaptable and removable water tank, Aeroccino and cup support
- Coffee settings: 25ml for Ristretto, 40 ml for espresso, 110ml for Lungo
- Compatible with Macchiato Glass
- Recycled plastic: 1/3 of plastic not in contact with food is post-consumer recycled
- Indication of empty water tank and full used capsule container
- Energy label: classed A- 40% (according to Swiss FEA label) thanks to the automatic OFF mode. Manufacturer settings: 9 min after last coffee preparation/operation or 9 min. after turning on if no operation. It can be changed to 30 min by consumer. Manual OFF mode at any time.
- Program for descaling procedure and low frequency descaling needs
- Convenient Power cable storage
- Fast heat up time: 25 seconds
- capsule container full and water empty alert

- Machine finish
    - Cover: ABS with embossed Nespresso logo
    - Housing: Recycled ABS
    - Drip grid: ABS
    - Slider: tri-componet Zamak – ABS - caoutchouc
    - Cup support : ABS with Stainless Steel insert
    - Aeroccino3: Stainless Steel/Plastic Black Matt
- Aeroccino3: integrated milk frothing device
    - Preparation time for milk froth (120ml): 60 - 90 seconds
    - Preparation time for cold milk froth (120 ml): 70 - 90 seconds
    - Preparation time for hot milk (240ml): 120 -180 seconds
- Easy cleaning of the Aeroccino: non-sticking ceramic coating

Technical indications

Country of origin	Hungary
Pump static pressure	19 bar
Water tank capacity	0.8 liter
Coffee machine Power	Refer to CPD
Capacity	240ml for hot milk and 120ml for milk froth
Cable length	EU 0.8m; UL 0.9 m; Japan 1.20m
Capsule container capacity	12 capsules
Drip tray capacity	120 ml
Pre-heating time for coffee (cold machine)	25-30s (depending on voltage and outside temperature)
Machine dimensions	L 342 x W 236 x H251 mm (Aero/Water tank in V position) L 370 x W 195 x H251 mm (Aero/Water tank in L position)
Machine Weight	~4kg (without packaging)
Packaging dimensions	374x274x315.5 (LxWxH)
Brown outercase weight (2 machines inside)	9.3kg
Brown outercase dimensions (2 machines inside)	558x381x323 (LxWxH)