

## ZENIUS MACHINE IN TANK WATER FILTER CARTRIDGE REPLACEMENT PROCEDURE















You may refer to the machine assistance [videos](#) on the **Nespresso** Professional website for guidance.

### Optional In-Tank Water Filter (if fitted to Zenius)

If you are using optional in-tank water filters on your Zenius machine, and you are restarting the machine after a period of business shutdown, please replace existing in-tank filter with a new one.

Simply follow the steps to the 'Filter cartridge exchange procedure' below.

Note: Optional in-tank water filters for Zenius machines are not included with new machine and not a part stocked/supplied by **Nespresso** Professional.

					
<p>Empty water tank.</p>	<p>Remove used water filter cartridge and discard it.</p>	<p>Clean and flush water tank with a soft towel.</p>	<p>Remove the new filter from its packaging.</p>	<p>Using a coin or something similar to a coin, turn the dial anticlockwise.</p>	<p>The window on the dial should begin with the current month e.g. 5 for May. Life time of the filter is 4 months.</p>
					
<p>Insert the water filter cartridge in the water tank.</p>	<p>Fill water tank with fresh potable water and insert in the coffee machine.</p>	<p>Dispense 800mL of hot water using the 'Hot Water' button on the machine.</p>	<p>Switch off the main power button.</p>	<p>Press and hold 'Hot Water' button while turning on the machine.</p>	<p>Observe blinking cycle on the machine.</p>
					
<p>To select new filter, press 'Ristretto' during blinking cycle.</p>	<p>Confirmation of selection: New filter is selected.</p>	<p>About 150mL cold water flows out of the hot water outlet within approx. 50 seconds.</p>			